



Features

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Top plate/cover improved, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), WIFI optional, I FEEL, Pipes and cables

Capacity			12000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	3500(800-3800) 3800(1000-4200)	
Power input		W	1180(100-1600) 1100(300-1600)	
Current input		A	5.6(0.7-7.8) 4.9(0.6-6.4)	
SEER-SCOP/ Energy Class		W/W	6,19/A++ 4,03/A+	
Operating range		(°C)	16~49°C -15~30°C	
Energy consumption (per year, based on standard test results)		kwh	198 938	
Dehumidifying		Kg/h	1	
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	1900	
Max. current		A	9,5	
Compressor		Model	KSN98D34UER3	
		Type	DC	
		Brand	GMCC	
Indoor	Fan motor	Model	YYK18-4B	
		Power input	W	/
		Capacity	uF	1,5
		Indoor Fan Speed RPM	r/min	1280/1130/990/850
	Indoor fan	Dia. / Length	mm	φ97.8*558
	Indoor Air Circulation		m ³ /h	600
	Indoor Noise Level dB		dB(A)	53
	Net Dimension (L×W×H)		mm	705×285×200
	Packing Dimension (L×W×H)		mm	802×346×267
Net Weight/Gross Weight		Kg	8,5/10,5	
Outdoor	Fan motor	Model	D-35-10A	
		Power input	W	48
		Capacity	uF	/
		Outdoor Fan Speed RPM	r/min	920/700/540
	Outdoor fan	Length	mm	407
	Outdoor Noise Level dB		dB(A)	62
	Net Dimension (L×W×H)		mm	705×279×530
	Packing Dimension (L×W×H)		mm	825×326×595
	Net Weight/Gross Weight		Kg	22.5/26
	Refrigerant type/weight		g	R32/560
Max. Discharge/Max. Suction pressure		Mpa	4.3/2.5	
Refrigerant piping		Liquid side / Gas side	mm	φ6,35/φ9,52
		Max. refrigerant pipe length / Max. difference in level	m	20/10